

Single Phase - 480 X 600 Volt

Input & Output Voltages (Nominal)

Line - Line

480
600

Frequency (Hz)

50 / 60
60

Selectable Output Voltage

430 to 530
520 to 660

Narrow Range

Input Correction Range: -16% to +8% of selected output voltage

403 to 518 volts with the output set at 480 volts
504 to 648 volts with the output set at 600 volts

Rated Load		kVA at 600 V	Model Number (base unit)	Max. Input Amps	Recovery Rate † (seconds / %)	Approximate Weights				Enclosure
Amps	kVA at 480 V					Pounds		Kilograms		
						Net	Ship	Net	Ship	
Floor Mount Units										
60	29	36	WHR26NSX12	70	0.140	344	394	156	179	C
120	55	70	WHR26NSX14	140	0.210	544	594	247	269	E
180	85	105	WHR26NSX16	210	0.210	727	777	330	352	F
240	115	145	WHR26NSX24	280	0.270	946	1,046	429	474	DPLUS
300	145	175	WHR26NSX25	350	0.410	1,120	1,220	508	553	EPLUS
360	175	200	WHR26NSX26	420	0.410	1,329	1,429	603	648	FPLUS
420	200	250	WHR26NSX27	490	0.410	1,461	1,561	663	708	FPLUS
480	225	275	WHR26NSX28	560	0.820	1,593	1,693	723	768	FPLUS
540	250	325	WHR26NSX29	630	0.820	1,784	1,884	809	855	GPLUS
720	350	425	WHR26NSX38	840	0.820	2,287	2,387	1,037	1,083	FF
19-Inch Rack Mount Units										
# 60	29	36	WHR26NSX12R-CB	70	0.140	187	217	85	98	R2

Wide Range

Input Correction Range: -25% to +12% of selected output voltage

360 to 538 volts with the output set at 480 volts
450 to 672 volts with the output set at 600 volts

Rated Load		kVA at 600 V	Model Number (base unit)	Max. Input Amps	Recovery Rate † (seconds / %)	Approximate Weights				Enclosure
Amps	kVA at 480 V					Pounds		Kilograms		
						Net	Ship	Net	Ship	
Floor Mount Units										
33	16	20	WHR26WSX12	45	0.082	344	394	156	179	C
67	32	40	WHR26WSX14	90	0.120	544	594	247	269	E
100	48	60	WHR26WSX16	135	0.160	727	777	330	352	F
130	64	80	WHR26WSX24	180	0.160	946	1,046	429	474	DPLUS
165	80	100	WHR26WSX25	225	0.250	1,120	1,220	508	553	EPLUS
200	95	120	WHR26WSX26	270	0.250	1,329	1,429	603	648	FPLUS
230	110	140	WHR26WSX27	315	0.250	1,461	1,561	663	708	FPLUS
265	125	160	WHR26WSX28	360	0.490	1,593	1,693	723	768	FPLUS
300	140	180	WHR26WSX29	405	0.490	1,784	1,884	809	855	GPLUS
400	190	240	WHR26WSX38	540	0.490	2,287	2,387	1,037	1,083	FF
19-Inch Rack Mount Units										
# 33	16	20	WHR26WSX12R-CB	45	0.082	187	217	85	98	R2

Notes:

Listed model numbers, weights and enclosures are for base units. Options may increase weights and enclosure sizes.

These are 19 inch rack mounted units equipped with an input circuit breaker. Other options are only available on a special order basis; contact factory.

† Recovery rates shown are for 60 Hz operation. For 50 Hz, multiply by 1.2.